

AD-A132 808

NUMERICAL SOLUTION OF FREE BOUNDARY PROBLEM FOR
UNSTEADY SLAG FLOW IN THE..(U) WISCONSIN UNIV-MADISON
MATHEMATICS RESEARCH CENTER M NATORI ET AL. JUN 83

1//


UNCLASSIFIED

MRC-TSR-2536 DAAG29-80-C-0041

F/G 12/1

NL

END
DATE
FILMED
DTIC



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS - 1963 - A

AD-A132808

MRC Technical Summary Report # 2536

NUMERICAL SOLUTION
OF FREE BOUNDARY PROBLEM
FOR UNSTEADY SLAG FLOW IN THE HEARTH

Makoto Natori and Hideo Kawarada

Mathematics Research Center
University of Wisconsin-Madison
610 Walnut Street
Madison, Wisconsin 53706

June 1983

(Received June 14, 1983)

DTIC FILE COPY

Approved for public release
Distribution unlimited

Sponsored by

U. S. Army Research Office
P. O. Box 12211
Research Triangle Park
North Carolina 27709

DTIC
ELECTE
SEP 23 1983
E

88 09 22 130

UNIVERSITY OF WISCONSIN - MADISON
MATHEMATICS RESEARCH CENTER

NUMERICAL SOLUTION OF FREE BOUNDARY PROBLEM
FOR UNSTEADY SLAG FLOW IN THE HEARTH

Makoto Natori* and Hideo Kawarada**

Technical Summary Report #2536

June 1983

ABSTRACT

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input checked="" type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By _____	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A	



A numerical method for solving a problem in unsteady slag flow in the hearth of a blast furnace is presented. This problem is reduced to a free boundary problem for an elliptic system. The potential problem for a given free boundary is approximated by the penalty method. The derivatives of the potential function on the free boundary is approximated by the integration of the penalty term, and then the subsequent shape of the free boundary is obtained by solving the differential equation for the motion of the free boundary. The finite difference method is used to solve the penalized problem. A numerical example is given.

AMS (MOS) Subject Classifications: 34E05, 34E99, 35J05, 35J67, 35R35, 39A99

Key Words: Elliptic boundary value problems with discontinuous coefficients,
Penalty methods, Method of integrated penalty, Free boundary
problems

Work Unit Number 3 - Numerical Analysis and Scientific Computing

* Institute of Information Sciences and Electronics, University of Tsukuba,
Sakura-mura, Ibaraki 305, Japan.

** Department of Applied Physics, Faculty of Engineering, University of Tokyo,
Bunkyo-ku, Tokyo 113, Japan.

Sponsored by the United States Army under Contract No. DAAG29-80-C-0041.

- a -

NUMERICAL SOLUTION OF FREE BOUNDARY PROBLEM
FOR UNSTEADY SLAG FLOW IN THE HEARTH

Makoto Natori* and Hideo Kwarada**

1. INTRODUCTION

We present a numerical method for solving a problem in unsteady flow of molten slag in the hearth region of iron producing blast furnaces during the tapping operation [1]. This problem is reduced to a free boundary problems for an elliptic system. This type of problem is similar to the porous flow of underground water in which the water surface is a free boundary. The numerical calculations of this type of problem were done by various researchers [2 - 5]. The three-dimensional problem of the slag flow in the hearth was solved by using the finite element method by Ichihara and Fukutake [6]. They concluded that their computation scheme is not efficient in practical use.

The object of this paper is to resolve this computational instability by using the penalty method developed by Kwarada and Natori [7 - 10].

2. FORMULATION

We consider two-dimensional slag flow in the hearth which is bounded by impermeable boundaries $y = 0$, $x = 0$ and $x = a$. One of vertical boundaries, $x = 0$, has a tapping hole near the bottom. As shown in Figure 1, $y = g(x, t)$ denotes the free surface of the slag region Ω_g :

* Institute of Information Sciences and Electronics, University of Tsukuba, Sakura-mura, Ibaraki 305, Japan.

**

Department of Applied Physics, Faculty of Engineering, University of Tokyo, Bunkyo-ku, Tokyo 113, Japan.

$$\Omega_g = \{(x,y) \mid 0 < x < a, 0 < y < g(x,t)\} .$$




Figure 1

A velocity potential can be defined by

$$\phi = \frac{p}{\gamma} + y$$

where p is the fluid pressure and γ is the specific weight of the fluid.

If it is assumed that Darcy's law holds, the potential is given by

- (1) $\Delta \phi = 0$ in Ω_g
- (2) $\phi = y$ on $y = g(x,t)$
- (3) $\phi_y = 0$ on $y = 0$
- (4) $\phi_x = 0$ on $x = 0$ and $x = a$, except on the tapping hole
- (5) $\phi_x = k$ (> 0) on the tapping hole

where k is a constant.

The motion of the free surface is given by

$$(6) \quad g_t = (\phi_x g_x - \phi_y) |_{y=g(x,t)}.$$

The initial shape of the free surface, $y = g(x,0)$, is given and forms an initial condition for equation (6).

When we try to solve the problem formulated above, we must get a numerical solution of the potential problem (1) - (5) for a given free boundary $y = g(x,t)$. When this is done, the derivatives of the potential function can be calculated on the free boundary, and then the subsequent shape of the free boundary is obtained by solving the equation (6).

If we use the method of the integrated penalty to solve the potential problem, then the derivatives of the potential function on the free boundary are easily approximated [10, 11]. This is the reason for our application of the penalty method to the free boundary problems.

3. PENALTY METHOD

3.1. Penalized problem

We define the characteristic function $\chi^\varepsilon(x,y,t)$ such as

$$(7) \quad \chi^\varepsilon(x,y,t) = \begin{cases} 1 & \text{in } \Omega - \Omega_g^\varepsilon \\ 0 & \text{in } \Omega_g^\varepsilon \end{cases}$$

where the domains Ω_g^ε and Ω , which includes Ω_g^ε , are defined by

$$\Omega_g^\varepsilon = \{(x,y) \mid 0 < x < a, 0 < y < g^\varepsilon(x,t)\}$$

and

$$\Omega = \{(x,y) \mid 0 < x < a, 0 < y < b\}$$

as shown in Figure 2. Here $y = g^\varepsilon(x,t)$ is the approximate free boundary defined later.




Figure 2

By the use of χ^ϵ , equation (1) is approximated by

$$(8) \quad \Delta \phi^\epsilon - \frac{1}{\epsilon} \chi^\epsilon (\phi^\epsilon - y) = 0 \quad \text{in } \Omega,$$

where ϵ is a positive constant. We add a new boundary condition:

$$(9) \quad \phi^\epsilon = y \quad \text{on } y = b,$$

to the boundary conditions (3) - (5).

In fact, if we let ϵ be sufficiently small then we know that ϕ^ϵ approximates ϕ in Ω_g^ϵ and ϕ^ϵ is nearly equal to y in $\Omega - \Omega_g^\epsilon$ [12]. Therefore the boundary condition (2) is approximately satisfied.

If we use the method of integrated penalty, equation (6) is approximated by

$$(10) \quad g_t^\epsilon = -(1 - \frac{1}{\epsilon} \int_0^b \chi^\epsilon (\phi^\epsilon - y) dy) \quad .$$

This equation is obtained as follows. We put

$$p^\varepsilon = p^\varepsilon(x, y) = \frac{1}{\varepsilon} \chi^\varepsilon(\phi^\varepsilon - y) ,$$

$$q^\varepsilon = q^\varepsilon(x, y) = \int_y^b p^\varepsilon(x, \eta) d\eta .$$

By an application of Theorems 1.1 and 1.2 in [11], we have

$$p^\varepsilon \rightarrow \frac{\partial \psi}{\partial n} \Big|_{y=g(x,t)} \sqrt{1 + g_x^2} \frac{\partial \chi}{\partial y} \text{ in } \mathcal{D}'(\Omega) ,$$

$$q^\varepsilon \rightarrow - \frac{\partial \psi}{\partial n} \Big|_{y=g(x,t)} \sqrt{1 + g_x^2} (1 - \chi) \text{ in } \mathcal{D}'(\Omega) ,$$

as $\varepsilon \rightarrow 0$ and

$$q^\varepsilon(x, g^\varepsilon(x, t)) \simeq - \frac{\partial \psi}{\partial n} \Big|_{y=g(x,t)} \sqrt{1 + g_x^2} ,$$

where n is outward normal to Ω_g and

$$\psi = \begin{cases} \phi - y & \text{in } \Omega_g \\ 0 & \text{in } \Omega - \Omega_g . \end{cases}$$

Then we have

$$\begin{aligned} (\phi_x g_x - \phi_y) \Big|_{y=g(x,t)} &\simeq -1 - \sqrt{1 + g_x^2} \frac{\partial \psi}{\partial n} \Big|_{y=g(x,t)} \\ &\simeq -1 + q^\varepsilon(x, g^\varepsilon(x, t)) \\ &\simeq -1 + \frac{1}{\varepsilon} \int_0^b \chi^\varepsilon(\phi^\varepsilon - y) dy . \end{aligned}$$

Substituting this approximation into (6) we have (10). Now, the second term in the right hand side of (10) is called the integrated penalty.

3.2. Discretization of the penalized problem

The penalized problem (8) with the boundary conditions (3) - (5) and (9) is discretized by the finite difference method. Also the free boundary equation (10) is solved by Euler's method. The intervals $0 \leq x \leq a$ and $0 \leq y \leq b$ are divided into N and M equal subintervals of width h . The mesh size of time is denoted by Δt . We use the following notations in the discrete system:

$$\begin{aligned}
x_i &= ih, \quad 0 \leq i \leq N \\
y_j &= jh, \quad 0 \leq j \leq M \\
t_k &= k\Delta t, \quad 0 \leq k \\
\phi_{i,j,k} &= \phi^\varepsilon(x_i, y_j, t_k) \\
g_{i,k} &= g^\varepsilon(x_i, t_k) \\
\chi_{i,j,k} &= \chi^\varepsilon(x_i, y_j, t_k) .
\end{aligned}$$

We define the discrete characteristic function by

$$(11) \quad \chi_{i,j,k} = \begin{cases} 1 & j > [g_{i,k}/h] \\ \frac{1 - \rho_{i,k}}{1 + \frac{h^2}{4\varepsilon} \rho_{i,k}} & j = [g_{i,k}/h] \\ 0 & j < [g_{i,k}/h] \end{cases}$$

where $[]$ denotes the Gauss symbol and

$$\rho_{i,k} = g_{i,k}/h - [g_{i,k}/h] .$$

If we apply five points formula for the Laplacian, we have the following equations the potential function $\phi_{i,j,k}$ satisfies for any k ,

$$\begin{aligned}
(12) \quad & (4 + \frac{h^2}{\varepsilon} \chi_{i,j,k}) \phi_{i,j,k} - \phi_{i-1,j,k} - \phi_{i+1,j,k} \\
& - \phi_{i,j-1,k} - \phi_{i,j+1,k} = \frac{h^2}{\varepsilon} y_j \chi_{i,j,k} \\
& (0 \leq i \leq N, 0 \leq j \leq M) .
\end{aligned}$$

This system of linear equations is solved by the incomplete Cholesky decomposition combined with conjugate gradient method [13].

The free boundary $g_{i,k}$ is obtained by

$$(13) \quad g_{i,k+1} = g_{i,k} + \Delta t F(g_{i,k}) \quad (0 \leq i \leq N, 0 \leq k) ,$$

$$(14) \quad F(g_{i,k}) = -1 + \frac{h}{\varepsilon} \sum_{j=0}^M \chi_{i,j,k} (\phi_{i,j,k} - y_j) .$$

It should be noted that $\chi_{i,j,k}$ and $\phi_{i,j,k}$ are determined by $g_{i,k}$.

3.3. How to choose the penalty parameter ϵ

We assume ϵ is expressed by

$$(15) \quad \epsilon = h^\sigma \quad (\sigma > 0)$$

and try to find an optimal value of σ to minimize the difference of the right sides of equations (6) and (14). For this purpose, we consider a simple test problem:

$$(16) \quad \begin{cases} \Delta u = 0 & \text{in } \Omega_g \\ u = 1-y & \text{on } x = 0 \\ u = 1-x & \text{on } y = 0 \\ u = 0 & \text{on } y = 1-x \end{cases}$$

This problem has an exact solution:

$$u = 1 - x - y$$

in Ω_g (see Figure 3).




Figure 3

Therefore,

$$(17) \quad -\sqrt{1 + g_x^2} \frac{\partial u}{\partial n} \Big|_{y=g(x)} = 2 ,$$

where $g(x) = 1-x$.

Here we construct the discretized problem (P_h^ε) of the penalized equation (P^ε) :

$$(18) \quad \Delta u^\varepsilon - \frac{1}{\varepsilon} \chi u^\varepsilon = 0 \quad \text{in } \Omega$$

where

$$\chi = \begin{cases} 1 & \text{in } \Omega - \Omega_g \\ 0 & \text{in } \Omega_g \end{cases} .$$

We investigate the difference between (17) and the integrated penalty:

$$q_i^\varepsilon = \frac{h}{\varepsilon} \sum_{j=0}^M \chi_{i,j} u_{i,j}$$

by varying the value of σ in (15). We find that the optimal value of σ is $3 \sim 4$ for $1/8 \leq h \leq 1/16$.

3.4. Stability condition

Here we study the stability condition of (13). It is well known [14] that the stability condition is

$$(19) \quad \Delta t \left| \frac{\partial F}{\partial g} \right| \leq 2 ,$$

where

$$F(g) = -1 + \frac{1}{\varepsilon} \int_0^b \chi^\varepsilon(g) (\phi^\varepsilon(g) - y) dy .$$

If we use the property:

$$|\phi^\varepsilon(x, g(x, t))| \leq C_0 \sqrt{\varepsilon} ,$$

where C_0 is a constant independent of ε [15], then we have

$$|F(g) - F(\bar{g})| \leq \frac{C_0}{\sqrt{\varepsilon}} |g - \bar{g}| .$$

If we substitute $C_0/\sqrt{\varepsilon}$ to $|\partial F/\partial g|$ in (19), then we have

$$0 < \Delta t \frac{C_0}{\sqrt{\epsilon}} \leq 2 .$$

Therefore we may choose

$$(20) \quad \Delta t = C_1 \sqrt{\epsilon} = C_1 h^{\sigma/2} .$$

4. NUMERICAL EXAMPLE

In this section we present results for the problem (1) - (6), obtained by the method of integrated penalty. Data of the problem are as follows:

$$a = 1$$

$$b = 0.3125$$

$$k = 0.625 .$$

The tapping hole is located at $(0, 1/16)$. The initial surface is given by

$$g(x, 0) = 0.25 .$$

The parameters used for the numerical calculations are

$$h = 1/16$$

$$\epsilon = h^3 = 1/4096$$

$$\Delta t = \sqrt{\epsilon} = 1/64 .$$

In Figure 4 we show the results.




Figure 4

REFERENCES

- [1] J. M. Burgess et. al.: Lateral Drainage of Packed Bed, 8th National Chemical Engineering Conference, Melbourne, August 1980.
- [2] C. Balocchi et. al.: Free Boundary Problems in the Theory of Fluid Flow Through Porous Media: A Numerical Approach, *Calcolo*, 10 (1973) 1-86.
- [3] M. Natori and H. Kawarada: Numerical Solutions of Free Boundary Problem for Fluid Flow Through Porous Media, Report of the Computer Centre, University of Tokyo, 5 (1976) 1-6.
- [4] J. C. Bruch: A Survey of Free Boundary Value Problems in the Theory of Fluid Flow Through Porous Media: Variational Inequality Approach - Part I and II, *Advances in Water Resources*, 3 (1980) 65-80 and 115-124.
- [5] H. Rasmussen and D. Salhani: Unsteady Porous Flow with a Free Surface, *IMA J. APPL. MATH.*, 27 (1981) 307-318.
- [6] I. Ichihara and T. Fukutake: Numerical Calculation of Unsteady Slag Flow in the Blast Furnace Hearth During Tapping, *SYSTEMS*, Publication of Japan UNIVAC Users Association, 39 (1979) 39-45.
- [7] H. Kawarada and M. Natori: On Numerical Solutions of Stefan Problem I, *Memoirs of Numerical Mathematics*, 1 (1974) 43-54.
- [8] H. Kawarada and M. Natori: On Numerical Solutions of Stefan Problem II. Unique Existence of Numerical Solution, *Memoirs of Numerical Mathematics*, 2 (1975) 1-20.
- [9] H. Kawarada and M. Natori: On Numerical Methods for the Stefan Problem by Means of the Finite Difference and the Penalty, *Functional Analysis and Numerical Analysis (Proc. Japan-France Seminar, JSPS, Tokyo, (1978)* 183-201.

- [10] M. Natori and H. Kawarada: An Application of the Integrated Penalty Method to Free Boundary Problems of Laplace Equation, Numer. Funct. Anal. and Optimiz., 3 (1981) 1-17.
- [11] H. Kawarada: Numerical Methods for Free Surface Problems by Means of Penalty, Lecture Notes in Math., 704, Springer-Verlag, 1979.
- [12] J. L. Lions: Perturbations Singulières dans les Problèmes aux Limites et en Contrôle Optimal, Lecture Notes in Math., 323, Springer-Verlag, 1973.
- [13] J. A. Meijerink and H. A. van der Vorst: An Iterative Solution Method for Linear Systems of Which the Coefficient Matrix is a Symmetric M-Matrix, Math. Comp., 31 (1977) 148-162.
- [14] P. Henrici: Discrete Variable Methods in Ordinary Differential Equations, John Wiley & Sons, 1962.
- [15] H. Kawarada: Numerical Solution of Free Boundary Problem for an Ideal Fluid, 4th International Symposium on Computing Method in Applied Sciences and Engineering, Versailles, December 1979.

MN/HK/jvs

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER #2536	2. GOVT ACCESSION NO. AD-A132808	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Numerical Solution of Free Boundary Problem for Unsteady Slag Flow in the Hearth		5. TYPE OF REPORT & PERIOD COVERED Summary Report - no specific reporting period
7. AUTHOR(s) Makoto Natori and Hideo Kawarada		6. PERFORMING ORG. REPORT NUMBER
9. PERFORMING ORGANIZATION NAME AND ADDRESS Mathematics Research Center, University of 610 Walnut Street Madison, Wisconsin 53706		8. CONTRACT OR GRANT NUMBER(s) DAAG29-80-C-0041
11. CONTROLLING OFFICE NAME AND ADDRESS U. S. Army Research Office P. O. Box 12211 Research Triangle Park, North Carolina 27709		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS Work Unit Number 3 - Numerical Analysis and Scientific Computing
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		12. REPORT DATE June 1983
		13. NUMBER OF PAGES 11
		15. SECURITY CLASS. (of this report) UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Elliptic boundary value problems with discontinuous coefficients, Penalty methods, Method of integrated penalty, Free boundary problems.		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) A numerical method for solving a problem in unsteady slag flow in the hearth of a blast furnace is presented. This problem is reduced to a free boundary problem for an elliptic system. The potential problem for a given free boundary is approximated by the penalty method. The derivatives of the potential function on the free boundary is approximated by the integration of the penalty term, and then the subsequent shape of the free boundary is obtained by solving the differential equation for the motion of the free boundary. The finite difference method is used to solve the penalized problem. A numerical example is given.		

**DAT
FILM**